

re PDE Please SAVE, FILL OUT, PRINT, SIGN and SUBMIT via EMAIL., FAX, or MAIL

COMPANY NAME: *	SIGNEE'S NAME: *		POSITION: *
DATE: *	PHONE NUMBER: *		EMAIL ADDRESS: *
□ - □ - □			
MONTH DAY YEAR			
The above mentioned company (hereinafter referred to as	"the Client") hereby gives the following warranti	es and indemnities to Pira	ates Press, Inc. (hereafter referred to as "PP"):
That the Client is the sole owner of the copyright in the material su	policed for reproduction, or alternatively that the Clin	ont has been granted the ric	abt to reproduce and distribute the material described
in the order by all copyright owners.		,	•
That the Client has not granted an exclusive License or Assignmer other party.	nt of the rights in clause 1 hereof to any other party	and that the material does	not infringe the copyright or any other rights of any
 That the material does not contain anything of an obscene or illegated. That the Client will keep PP fully indemnified against all losses and 		and all legal costs or other	r expenses arising out of any breach of any of the
above warranties. 5. That the Client agrees to provide PP on their request with all releva	, ,	•	
intellectual property at issue.		,	
That the Client agrees that despite any non-disclosure agreements concerning intellectual property rights ownership of the intellectual property.	roperty at issue.		bodies (i.e. IFPI, BSA, IRIMA, RIAA, BIAM, OSA, etc.)
 The Client agrees that PP may retain components or products for a 8. The Client agrees that by signing below, all information submitted 			omitting. PP is not responsible for mistakes made by
the Client when completing and submitting this Order Form. PP is no 9. The client agrees that the job will not be started by Pirates Press u			
10. The Client agrees that artwork must state "Manufactured in Czec		oulds order that been recei	
SIGNATURE: *			
Please sign your name within the box. By signing, you are agr	reeing to the terms listed above and are legally	acknowledging everythi	ing you fill out to be truthful and accurate.
COMPANY NAME: *			
ARTIST: *			
ALBUM TITLE: *			
ALBOM TITLE.			
04TALOG NUMBER #			
CATALOG NUMBER: *			
INTELLECTUAL PROPERTY RIGHTS: *	IF "NO." P	LEASE EXPLAIN:	
DICTRIDUTION: *	IE "OTHER	" DI EACE CDECIEV.	
DISTRIBUTION: *	IF "UTHER	R," PLEASE SPECIFY:	
COUNTRIES OF DISTRIBUTION: *	IF "COUN"	TRIES," PLEASE LIST:	
REQUESTED DELIVERY DATE (this is NOT a guarantee): *			
l	MONTH DAY YEAR		
AUTHORIZED FOR USE ON OUR "RECORD OF THE WEEK" BLO			
THE PLAN SELECTION OF THE PLAN DE			

Check this box to confirm you have read and understand Pirates Press "Terms & Conditions."

/ <u>**</u>	PINATES PRESS • 1200 PUWELL ST. • EWENT VIL
	TRACKLISTING F

ARTIST:	TITLE:		CATALOG NUMBER:
VINYL SIZE / WEIGHT: *	IF "OTHER," PLEASE SPECIFY:		QUANTITY:
TEST PRESSINGS?: * YES NO	SPECIFY # of TEST PRESSINGS? (min. # of 5)		
CUSTOM RUN-OUT YES NO SIDE A: [Up to 55	characters]		
SIDE B: [Up to 55	characters]		
MASTER SOURCE: *	GENRE: *	IF "OTI	HER," PLEASE SPECIFY:
Pre-mastered for vinyl *	Specific gap (silence) in master indication	ng the side split *	
TRACKLISTING: * FILL OUT TRACKLISTING ATTACH	PQ SHEET		
SIDE A TRACKLISTING SELECT SPEED: * 33 RPM	45 RPM N/A (Please explain)		
TRACK# SONG TITLE		LENGTH STA	ART END
Track 1			
Track 2			
Track 3			
Track 4			
Track 5			
Track 6			
Track 7			
Track 8			
Track 9			
Track 10			
SIDE B TRACKLISTING SELECT SPEED: * 33 RPM	45 RPM N/A (Please explain)		
TRACK # SONG TITLE		LENGTH ST/	ART END
Track 1			
Track 2			
Track 3			
Track 4			
Track 5			
Track 6			
Track 7			
Track 8			
Track 9			
Track 10			

<u> </u>	PIRATES PRESS • 1200 PUWELL ST. • EWERT	VILL
	TRACKLISTING	F

ARTIST:	TITLE:		CATALO	G NUMBER:
VINYL SIZE / WEIGHT: *	IF "OTHER," PLEASE SPECIFY:		QUANTI	ГҮ:
TEST PRESSINGS?: * YES NO	SPECIFY # of TEST PRESSINGS? (min. # of 5)			
CUSTOM RUN-OUT YES NO SIDE C: [Up to 55 of GROOVE ENGRAVING?: *	characters]			
SIDE D: [Up to 55	characters]			
MASTER SOURCE: *	GENRE: *	IF "O	THER," PLEASI	SPECIFY:
Pre-mastered for vinyl *	Specific gap (silence) in master indicating	the side split *		
TRACKLISTING: * FILL OUT TRACKLISTING ATTACH F	PQ SHEET			
SIDE C TRACKLISTING SELECT SPEED: * 33 RPM (45 RPM N/A (Please explain)			
TRACK # SONG TITLE		LENGTH S	START	END
Track 1				
Track 2				
Track 3				
Track 4				
Track 5				
Track 6				
Track 7				
Track 8				
Track 9				
Track 10				
SIDE D TRACKLISTING SELECT SPEED: * 33 RPM (45 RPM N/A (Please explain)			•
TRACK # SONG TITLE		LENGTH S	TART	END
Track 1				
Track 2				
Track 3				
Track 4				
Track 5				
Track 6				
Track 7				
Track 8				
Track 9				
Track 10				

<u> </u>	PIRATES PRESS • 1200 PUWELL ST. • EWERT	VIL
	TRACKLISTING	F

ARTIST:	TITLE:		CATALOG NUMBER:
VINYL SIZE / WEIGHT: *	IF "OTHER," PLEASE SPECIFY:		QUANTITY:
TEST PRESSINGS?: * YES NO	SPECIFY # of TEST PRESSINGS? (min. # of 5)		
CUSTOM RUN-OUT YES NO SIDE E: [Up to 55 GROOVE ENGRAVING?: *	characters]		
SIDE F: [Up to 55	characters]		
MASTER SOURCE: *	GENRE: *	IF "OTHER	R," PLEASE SPECIFY:
Pre-mastered for vinyl *	Specific gap (silence) in master indicating	the side split *	
TRACKLISTING: * FILL OUT TRACKLISTING ATTACH	PQ SHEET		
SIDE E TRACKLISTING SELECT SPEED: * 33 RPM	45 RPM N/A (Please explain)		
TRACK # SONG TITLE		LENGTH START	Γ END
Track 1			
Track 2			
Track 3			
Track 4			
Track 5			
Track 6			
Track 7			
Track 8			
Track 9			
Track 10			
SIDE F TRACKLISTING SELECT SPEED: * 33 RPM	45 RPM N/A (Please explain)		
TRACK# SONG TITLE		LENGTH START	Γ END
Track 1			
Track 2			
Track 3			
Track 4			
Track 5			
Track 6			
Track 7			
Track 8			
Track 9			
Track 10			

_/ ※	PIRATES PRESS • 1200 PUWELL ST. • EWERT	VILI
	TRACKLISTING	F

ARTIST:	TITLE:		CATALO	G NUMBER:
VINYL SIZE / WEIGHT: *	IF "OTHER," PLEASE SPECIFY:		QUANT	ITY:
TEST PRESSINGS?: * YES NO	SPECIFY # of TEST PRESSINGS? (min. # of 5			
CUSTOM RUN-OUT YES NO SIDE E: [Up to 55 GROOVE ENGRAVING?: *	characters]			
SIDE F: [Up to 55	characters]			
MASTER SOURCE: *	GENRE: *	IF '	OTHER," PLEAS	E SPECIFY:
Pre-mastered "High volume* or vinyl * DMM cut" *		Specific gap (silence indicating the side s		
TRACKLISTING: * FILL OUT TRACKLISTING ATTACH I	PQ SHEET			
SIDE E TRACKLISTING SELECT SPEED: * 33 RPM (45 RPM N/A (Please explain)			
TRACK# SONG TITLE		LENGTH	START	END
Track 1				
Track 2				
Track 3				
Track 4				
Track 5				
Track 6				
Track 7				
Track 8				
Track 9				
Track 10				
SIDE F TRACKLISTING SELECT SPEED: * 33 RPM (45 RPM N/A (Please explain)			
TRACK # SONG TITLE		LENGTH	START	END
Track 1				
Track 2				
Track 3				
Track 4				
Track 5				
Track 6				
Track 7				
Track 8				
Track 9				
Track 10				



VINYL ORDER FORM

This is an interactive PDF. Please SAVE, FILL OUT, PRINT, SIGN and SUBMIT via EMAIL, FAX, or MAIL.

VINYL CONFIGURATIONS

- Please reference color / configuration, quality of each color / configuration, and color swatch numbers from our website.
- If choosing BLACK VINYL, please write in "black" as the swatch number.
- There is a 100 units minimum per color / configuration.

COLORED VINYL?: * YES NO					
VINYL COLOR / CONFIGURATION	QUANTITY	COLOR	SWATCH NUMBER(S)		
CENTER LABEL PRINTING: *			IF "PANTONE	," PLEASE SPECIFY:	IF "OTHER," PLEASE SPECIFY:
INNERSLEEVE TYPE: *					IF "OTHER," PLEASE SPECIFY:
INNERSLEEVE PRINTING: *			"PANTONE"/	"CMYK+PANTONE":	IF "OTHER," PLEASE SPECIFY:
INNERSLEEVE PAPER STOCK: *					IF "OTHER," PLEASE SPECIFY:
INNERSLEEVE PAPER FINISH: *					IF "OTHER," PLEASE SPECIFY:
INSERT TYPE: *					IF "OTHER," PLEASE SPECIFY:
INSERT PRINTING: *			"PANTONE"/	"CMYK+PANTONE":	IF "OTHER," PLEASE SPECIFY:
INSERT PAPER STOCK: *					IF "OTHER," PLEASE SPECIFY:
INSERT PAPER FINISH: *					IF "OTHER," PLEASE SPECIFY:
JACKET TYPE: *					IF "OTHER," PLEASE SPECIFY:
JACKET PRINTING: *			"PANTONE"/	"CMYK+PANTONE":	IF "OTHER," PLEASE SPECIFY:
JACKET PAPER STOCK: *				<u>.</u>	IF "OTHER," PLEASE SPECIFY:
JACKET PAPER FINISH: *					IF "OTHER," PLEASE SPECIFY:



VINYL ORDER FORM

PROTECTION TYPE:				IF "OTHER," I	PLEASE SPECIFY:
BARCODE OPTIONS:					
BARCODE PLACEMENT, if applicable:	BA 	ARCODE NUMBER, if appl	icable:		
MARKETING STICKER, if applicable. Please specify color specs (B&	&W, color, pantone), siz	ze, and placement below	١.		
DOWNLOAD CARD TYPE:				IF "OTHER," F	PLEASE SPECIFY:
ADDITIONAL PRINTWORK, if applicable. Options include obi-strip, o	o-card, slipcase, box s	set, etc.			
ADDITIONAL OUTSIDE PARTS to be inserted or applied to your orde	ər. ie. guitar pick, phot	o, embroidered patch, et	c.		
SHIPPING OPTION: *	IF "OTHER,"	PLEASE SPECIFY:	S	SHIPPING INSTRUCTIONS	*
] [
IF "LISTED ABOVE" OR "OTHER," PLEASE SPECIFY:					
CUIDDING: When pleasing your endow let up know if a significant new	which of vois and a will	ahin within Europa wa		manaul	
SHIPPING: When placing your order, let us know if a signficant por	ruon or your order will	Silip Within Europe - We	can save you	money:	
SPECIAL BOXING / LABELING CONFIGURATIONS, if applicable:					
ADDITIONAL COMMENTS, if applicable:					



GRAPHIC GUIDELINES & FILE SUBMISSION

TO ALLOW US TO PROVIDE YOU WITH THE BEST SERVICE POSSIBLE, PLEASE FOLLOW THE BELOW GUIDELINES IN SUBMITTING YOUR ART & AUDIO!

DESIGNING & SUBMITTING YOUR ARTWORK FILES

The accuracy of your source materials shall secure the problem-free processing of your order! For this reason we request that, in your own, you abide by the following conditions!

Incomplete, incorrect, or illegible art files will result in production delays and possibly poor presentation of final product. Have your artwork designed by a professional graphic designer. Unless you've arrange it with your sales representative beforehand, we require that all graphic materials are to be received in a Pirates Press template. We have templates available for almost everything we manufacture. Visit the "templates" page at <u>piratespress.com/art-templates</u> - if you are unsure which template to use, please contact your sales representative.

- ALL IMAGES MUST BE 300 D.P.I. RESOLUTION or higher.
- ALL IMAGES MUST BE CMYK and/or properly prepared PANTONE files. Do not submit pantones unless you've ordered them.
- Use ONLY PIRATES PRESS TEMPLATES. Always keep the template on its own later. NEVER FLATTER TEMPLATE to artwork.
- TEMPLATES are the actual die-cut. ADD 3mm (.125") to the die-cut lines.
- TEXT and LOGOS should not be closer thatn 3mm (.125") to the die-cut lines.
- EPS and PDF file formates EXTREMELY PREFERRED. PSD files are prone to problems are are RELUCTATLY ACCEPTED.
- QXD and INDD files are NOT ACCEPTED. NO GIF or JPEG files ever.
- ALL TEXT must be CONVERTED to OUTLINES (Illustrator, Quark, Indesign) or RASTERED / FLATTENED (Photoshop).
- ALL IMAGES must be EMBEDDED to OUTLINES (Illustrator, Quark, Indesign) or RASTERED / FLATTENED (Photoshop).
- SAVE your files as SINGLE ARCHIVES (.zip or .sit) named only with your CATALOG NUMBER and the word "ART" (ex. PPR023_ART.zip).
- ALL ART FILES should be UPLOADED from our WEB-BASED UPLOAD APPLICATION: piratespress.com/upload.
- YOU MUST include "MADE IN CZ" on your artwork visit piratespress.com/czmarking for more info.

*** Please fill out your order forms properly. Make sure the artwork you are submitting matches your order form and the sales order (or estimate) that you have received from your sales rep. If it doesn't, make sure it gets adjusted immediately to avoid delays in production.

MASTERING & SUBMITTING YOUR AUDIO FILES

Incomplete, incorrect, or illegible audio files will result in production delays, and possibly poor presentation of final product. Have your vinyl mastered by a professional mastering studio. Please instruct them to follow our "MASTERING FOR VINYL" specifications which can be found on the next page and further technical conditions can be found at <u>piratespress.com/vinyl-technical-conditions</u>.

- WAV or AIFF FILES ONLY, HIGH RESOLUTION 24 BIT WAV files are PREFERRED.
- MP3, M4A, and CDA files are NOT ACCEPTED.
- SAVE your files as SINGLE ARCHIVES (.zip or .sit) named only with your CATALOG NUMBER and the word MASTER (ex. PPR023 MASTER.zip).
- ALL AUDIO FILES should be submitted on (REDBOOK) CD MASTERS OR should be UPLOADED through our WEB-BASED UPLOAD APPLICATION: <u>piratespress.com/upload</u>

When we prepare to cut your record, if you sent the master as one track/file per side, we expect that the files contain gaps in between the tracks. We do not add gaps between the tracks in this case. If you request to have specific gaps added, it must be clearly mentioned in the supplied tracklisting. It is possible to request specific gaps depending on each song or the same gap length for all songs. If you supply your sides as one track/file per song, unless you specifically note otherwise on your tracklisting form, our studio will cut the tracks with standard 2-3 second gaps between tracks.

We have the ability to press records with playing times that exceed our recommended playing times. We assume no responsibility for any deterioration in sound quality when recommended playing times are exceeded. Claims based on sound quality when recommended playing times are exceeded are most likely to be rejected.

*** Please fill out tracklist form as completely as possible. Include any relevant / pertinent engineering notes so that our engineers have as much info as possible when cutting your records.



MASTERING FOR VINYL

To get the best results with your records, you need to read the following before preparing your master source. Following these instructions will ensure that you are satisfied with the final product.

The ultimate goal of your creation is not only the recording on your CD or cassette, but on vinyl, which you intend to offer to your fans. However, before the recording created by you is pressed, it has to go through many steps to ensure it is up to standard. It has its limitations – determinate limits, which result from the physical laws.

- 1. Try not to exceed the maximum recommended playing lengths per side, as longer playing times will lead to a dramatic decrease in recording level and dynamics. On the other hand, the requirements of extremely high recording levels decrease the possible playing time (see the table in the next section for recommended playing times for all formats).
- 2. Try to place demanding, powerful and exposed tracks at the beginning of the required side and not towards the end of the record. The conditions for recording and subsequent reading of vinyl records get worse with the decreasing diameter towards the middle of the record (the label).
- 3. Try to avoid using psycho acoustic processors to an excessive degree.
- 4. If possible, please check the master by using a correlation measurer (it must not be drastically in the red field or have negative values) and a frequency spectrum analyser to ensure the signal does not contain unreasonably large elements in the low frequency range (around 20 Hz) and also the top end of the frequency zone (around 20 kHz).
- 5. The lowest frequencies of the acoustic zone that are below 300 Hz have to be in phase.
- 6. Filter away all inaudible signals to avoid possible problems during recording and reproduction, e.g. subacoustic signals below 20 Hz (better below 40 Hz) and high frequencies above 16 kHz.
- 7. If your recording substantially differs from natural sounds, which is caused by spreading out the energy in the acoustic zone, there is a risk of audible changes to the sound during the transcription. This is due to the limitations of mechanical recording processes and can, for example, be caused by voice processors or electronically generated effects. In the worst scenario where the signal/music has such critical characteristics that it may damage the cutting head, the order will unfortunately be refused.
- 8. AS STANDARD we choose the highest reasonably possible level in accordance with the character of the existing recording and with respect to the specific properties of the mechanical recording. If it is tolerated by the limit values of the recorder and by the playing time of recording, then it is possible at Customer's express request (mostly DJ or rock and heavy-metal bands) to use a higher level LOUD, however on the side of reproduction it can be to the prejudice of distortion or stability of the tip.
- 9. Try to avoid 7" vinyl formats at 33 1/3 rpm as the possibilities of the recording and reproduction are most limited at this format. If there is no other solution you have to take into account that the final product will be in some way compromised *
- 10. Remember that good reproduction results on the user's side depend on the quality, technical conditions and correct adjustment of the reproduction facilities! **
- 11. We need a complete track list with your master containing the names of all tracks (including the hidden and bonus tracks), track timings and their separation into side A and side B, the total time of each side!!! Please inform us of any special effects or anomalies etc. Any orders without a complete track list will be refused for production.
- 12. Please carefully check if the data on the track list (number of tracks, track order, names and timings on each side) corresponds with the master, the label and cover artwork (and other printed parts inserts, posters).
- 13. Please keep in mind that the data needs to be readable and understandable.
- 14. Any claims against the final product, caused by errors in the production parts supplied by customer, will not be accepted!
- 15. If you require additional adjustments or mastering (changes in track order, disregarding some tracks, compilation....) please specify your request exactly on the order form, and note what is on the master and what needs to be done for the final product.
- * Low groove speed limits the recording level and causes a higher decrease of the high frequencies into the middle of the record and can also cause higher distortion levels.
- ** The quality of the reading system, the shape, the level of the attrition, the cleanness of the needle and the adjustment of the vertical force and anti-skating.

SUGGESTED MAXIMUM PLAYING TIMES (IN MINUTES)

VINYL SIZE	33 1/3 RPM	45 RPM
7"	8.0 - 8.5	6.0 - 6.5
10"	14.0 - 15.5	10.5 - 11.5
12"	18.0 - 20.0	14.0 - 15.5
FLEXI VINYL SIZE	33 1/3 RPM	45 RPM
5"	1.5 - 2.0	1.0 - 1.5
7"	3.0 - 6.0	1.0 - 3.0

^{*}It is applicable only in special cases, when it is not prevented by the frequency spectrum of recording and by limit values of the machine. A larger width of the groove than approximately 70 µm is feasible only on the lacquer foil, obviously to the prejudice of the attainable reproduction time, and with awareness of a certain damping on the high frequencies, especially at the center of the record, which is determined by the possibilities of lacquer technology.